



AMITY INSULATION GROUP INC.

14715 - 122 Avenue, Edmonton, Alberta Canada T5L 2W4

Bus: (780) 454-8558
Fax: (780) 452-2747

DATA SHEET

ALUMINUM & STAINLESS STEEL TWO-PIECE ELBOWS

Characteristics

Aluminum elbow covers are precision formed from .024" thick, 1100 alloy, meeting ASTM C-585 standards. The aluminum is coated with a heat cured enamel moisture barrier to resist electrolytic decomposition and oxidation. The elbow covers are manufactured as two matching halves to form a precise fit for 90 degree and 45 degree insulation elbows. The aluminum elbows are available in smooth finish only at this time. Please call to discuss embossed elbows. Gore elbows are available as well.



Stainless steel elbow covers are formed bare from .010" thick, type 304 and 316 stainless steel (special order). The elbows are manufactured to meet ASTM C-450 and fit 90 degree and 45 degree insulation elbows. Presently our stainless steel elbow covers are available in smooth finish only.

| 90° Aluminum | | | | | | |
|----------------|----------------------|------|------|------|------|------|
| Iron Pipe Size | Insulation Thickness | | | | | |
| | ½" | 1" | 1 ½" | 2" | 2 ½" | 3" |
| ½" | # 1 | # 2 | # 5 | # 8 | # 12 | # 23 |
| ¾" | # 1 | # 2 | # 5 | # 8 | # 12 | # 23 |
| 1" | | # 3 | # 6 | # 11 | # 12 | # 23 |
| 1 ¼" | | # 3 | # 9 | # 11 | # 18 | # 23 |
| 1 ½" | | # 4 | # 9 | # 18 | # 23 | # 59 |
| 2" | | # 7 | # 10 | # 18 | # 20 | # 15 |
| 2 ½" | | # 13 | # 16 | # 20 | # 24 | # 25 |
| 3" | | # 14 | # 19 | # 22 | # 24 | # 25 |
| 3 ½" | | # 17 | # 21 | # 27 | # 30 | # 33 |
| 4" | | # 17 | # 21 | # 27 | # 30 | # 33 |
| 4 ½" | | # 21 | # 27 | # 30 | # 33 | # 31 |
| 5" | | # 28 | # 29 | # 36 | # 38 | # 39 |
| 6" | | # 32 | # 35 | # 37 | # 39 | # 44 |
| 7" | | # 35 | # 37 | # 39 | # 44 | # 45 |
| 8" | | # 41 | # 42 | # 43 | # 47 | # 49 |
| 9" | | # 42 | # 43 | # 47 | # 49 | # 52 |
| 10" | | # 46 | # 50 | # 51 | # 55 | # 54 |

| 45° Aluminum | | | | | |
|----------------|----------------------|------|------|------|------|
| Iron Pipe Size | Insulation Thickness | | | | |
| | 1" | 1 ½" | 2" | 2 ½" | 3" |
| ½" | # 1 | # 3 | # 5 | # 7 | # 8 |
| ¾" | # 1 | # 3 | # 5 | # 7 | # 8 |
| 1" | # 2 | # 4 | # 6 | # 7 | # 8 |
| 1 ¼" | # 2 | # 5 | # 6 | # 7 | # 8 |
| 1 ½" | # 3 | # 5 | # 7 | # 8 | # 9 |
| 2" | # 4 | # 6 | # 7 | # 8 | # 9 |
| 2 ½" | # 5 | # 7 | # 8 | # 9 | # 10 |
| 3" | # 6 | # 7 | # 8 | # 9 | # 10 |
| 3 ½" | # 7 | # 8 | # 9 | # 10 | # 11 |
| 4" | # 7 | # 8 | # 9 | # 10 | # 11 |
| 4 ½" | # 8 | # 9 | # 10 | # 11 | # 12 |
| 5" | # 8 | # 9 | # 10 | # 11 | # 12 |
| 6" | # 9 | # 10 | # 11 | # 12 | # 13 |
| 7" | # 10 | # 11 | # 12 | # 13 | # 14 |
| 8" | # 11 | # 12 | # 13 | # 14 | # 15 |
| 9" | # 12 | # 13 | # 14 | # 15 | Gore |
| 10" | # 13 | # 14 | # 15 | # 16 | Gore |

| 90° Stainless Steel | | | | | |
|---------------------|----------------------|------|------|------|------|
| Iron Pipe Size | Insulation Thickness | | | | |
| | 1" | 1 ½" | 2" | 2 ½" | 3" |
| ½" | # 2 | # 5 | # 8 | # 12 | # 23 |
| ¾" | # 2 | # 5 | # 8 | # 12 | # 23 |
| 1" | # 3 | # 6 | # 11 | # 12 | # 23 |
| 1 ¼" | # 3 | # 9 | # 15 | # 16 | # 26 |
| 1 ½" | # 4 | # 9 | # 18 | # 23 | # 24 |
| 2" | # 7 | # 10 | # 18 | # 20 | # 25 |
| 2 ½" | # 13 | # 16 | # 20 | # 24 | # 31 |
| 3" | # 14 | # 19 | # 22 | # 24 | # 30 |
| 3 ½" | # 17 | # 21 | # 27 | # 30 | # 33 |
| 4" | # 17 | # 21 | # 27 | # 30 | # 33 |
| 4 ½" | # 28 | # 27 | # 30 | # 33 | # 40 |
| 5" | # 28 | # 29 | # 36 | # 38 | # 39 |
| 6" | # 32 | # 35 | # 37 | # 39 | # 44 |
| 7" | # 35 | # 37 | # 39 | # 44 | # 47 |
| 8" | # 41 | # 42 | # 43 | # 47 | # 50 |
| 9" | # 42 | # 43 | # 47 | # 50 | # 52 |
| 10" | # 46 | # 50 | # 50 | # 52 | # 53 |

Please refer to our printed price pages for the entire range of sizes

This information is representative at the time of publication and should not be deemed to constitute or imply any warranty of performance. The user is responsible for determining the suitability of the material for the respective application. All drawings, descriptions and photos remain Amity's exclusive property and cannot be used without the prior written consent of Amity management. This publication renders all previous copies invalid. Amity's sales policy is applicable at all times. Protherm is a registered trademark.