



Specialty Products, Inc.

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: LEWCO 3700SA-2, 1750SA-2 & 1700SA-2
Product Use Description: Silicone impregnated fiberglass fabrics for thermal insulation materials
Manufacturer/Distributor: Lewco Specialty Products, Inc.
6859 Renoir Avenue
Baton Rouge, LA 70806
Telephone: (800) 221-6414 TX & AR (800) 233-9755
(225) 924-3221 Fax (225) 927-2918
Emergency Telephone: Not available

2. HAZARDS IDENTIFICATION

GHS hazard classification

Health hazards: Skin corrosion/irritation, 2
Serious eye damage/eye irritation, 2A
Specific target organ toxicity - Single exposure, 3
Physical hazards: Not classified
Environmental: Not classified

GHS lab elements

Signal words: Warning
Hazard statements: H315, Causes skin irritation
H319, Causes serious eye irritation
H335, May cause respiratory irritation

Hazard pictograms/symbols:



Precautionary statements

(Prevention): P264, Wash...thoroughly after handling.
P280, Wear protective gloves/protective clothing/eye protection/face protection
(Response): P302 + P352, IF ON SKIN-Wash with plenty of soap and water.
P304 + P340, IF INHALED-Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338, IF IN EYES-Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312, Call a POISON CENTER or doctor/physician if you feel unwell.
P321, Specific treatment (see supplemental first aid on this label).
P332+313, If skin irritation occurs-Get medical advice/attention.
P337+313: If eye irritation persists-Get medical advice/attention.

P362, Take off contaminated clothing and wash before reuse.
P370+378, In case of fire: Use dry chemical, dry sand, carbon dioxide or alcohol-resistant foam to extinguish.

(Storage): Not applicable

(Disposal): P501, Dispose of contents/container in accordance with local regulation.

Description of any hazards not otherwise classified: Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS number	% by weight
Fiberglass Fabric	65997-17-3	70-80
Silicone coating	Not available	20-25
Aluminum trihydroxide	21645-51-2	1.5-3.5
Ground limestone	1317-65-3	1.5-3.5
Pigment (Aluminum powder)	7429-90-5	< 1.5

(See Section 8 for Exposure Limits)

4. FIRST AID MEASURES

Inhalation: Move individual to fresh air. Drink water to clear throat and blow nose to remove fibers. Seek medical attention if irritation persists.

Skin Contact: Wash with mild soap and running water: use a washcloth to help remove dust and fibers. To avoid further irritation do not rub or scratch irritated areas. Rubbing or scratching may force fibers into the skin. Seek medical attention if irritation persists.

Eye Contact: Flush eyes with flowing water for at least 15 minutes. Seek medical attention if irritation persists.

Ingestion: Drink extra water to assist natural elimination. Seek medical attention if gastrointestinal irritation persists or other symptoms such as nausea, vomiting, or abdominal pain occur.

Most important symptoms/effects-acute or delayed: Irritation of dusts and fibers may result in inflammation of the upper respiratory tract (mouth, nose and throat), and itch and temporary mechanical irritation on skin.

Immediate medical care and special treatment needed: Indication for physician: No specific medical precaution necessary.

5. FIRE FIGHTING MEASURES

Suitable extinguishing equipment: Foam, carbon dioxide (CO₂), dry chemical

Specific hazards: Thermal decomposition of fiber coating silicone may produce an irritating mixture of noxious/toxic smoke and fumes, carbon dioxide, and carbon monoxide.

Special protective equipment or precautions for firefighters: Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions and protective equipment:	Wear suitable protective clothing, gloves and eye/face protection.
Emergency procedures:	Evacuate personnel to safe areas. Provide sufficient ventilation.
Environmental precautions:	Textile glass products are ecologically harmless.
Cleanup procedures:	No need for special cleaning precautions or rules. Dispose of in accordance with appropriate laws and regulations.

7. HANDLING AND STORAGE

Handling:	Use adequate safety equipment (gloves, glasses, dust mask) in order to minimize the possible risk of contact with skin, mucous membrane and eyes and decrease irritations and allergies.
Storage:	Keep in manufacturer bag and store in a dry place. Avoid direct sun light.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure Limits

Component:	Limit/set by
Fibrous Glass	OSHA: TWA, 15 mg/m ³ (total nuisance dust) and 5 mg/m ³ (respirable nuisance dust); NIOSH, REL/TWA-5 mg/m ³ (total glass dust), and 3f/cc (respirable fibers).
Silicone	Not available
Aluminum trihydroxide	OSHA: TWA, 5 mg/m ³ (respirable dust)
Ground limestone	OSHA: TWA, 2 mg/m ³ (respirable dust)
Pigment	OSHA: 15 mg/m ³ PEL (total dust)

Engineering controls

Ventilation:	General dilution ventilation and/or local exhaust ventilation should be provided, as necessary to maintain exposures below OSHA's limitation
--------------	--

Personal protective Equipment

Respiratory Protection:	A properly fitted NIOSH/MHSA approved disposable dust respirator (TC-21C-132) should be used when: the level of dust in the air exceeds permissible exposure limits; or if irritation occurs. Use respiratory protection in accordance with your company's respiratory protection program and OSHA regulations under CFR
Hand Protection:	Wear gloves when handling this product, and wash thoroughly with soap and water after handling materials.
Eye Protection:	Safety glasses, goggles or face shields should be worn whenever materials are being handled.
Protective Clothing:	Wear loose fitting, long sleeved shirt and long pants if irritation is experienced.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Solid, Silver
Upper/lower flammability or explosive limits:	Not available
Odor:	No odor
Vapor pressure:	Not available
Odor threshold:	Not available
Vapor density:	Not available

pH:	Not available
Relative density Specific Gravity (H₂O=1):	2.4
Melting point:	> 1,500 °F (fibrous glass)
Solubility(ies):	Not soluble in water
Initial boiling point and boiling range:	Not available
Flash point:	Not available
Evaporation rate:	Not available
Flammability (solid, gas):	Not available
Partition coefficient(n-octanol/water):	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	> 300 °F (coating)
Viscosity:	Not available

10. STABILITY AND REACTIVITY

Chemical Stability:	Product is stable under normal conditions of use
Conditions to avoid:	Not available
Materials to avoid:	Strong acid, strong bases, strong oxidizing agents
Hazardous decomposition products:	If the material is heated, residual proprietary organic ingredients contained in this product may produce smoke and irritating fumes including carbon monoxide and carbon dioxide, SiO ₂ . Contact with acids or bases releases flammable hydrogen gas.
Possibility of hazardous reactions/reactivity:	Not available

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Textile glass products do not contain hazardous or toxic ingredients
Chronic toxicity/effects from short- and long-term exposure:	Not available
Acute toxicity:	Not available
Carcinogens:	Textile glass products are not carcinogenic. They have a nominal filament diameter of 9µm. The smallest possible filament diameter is 6µm. According to the TRGS 905 (April 1996) fine fiber dust can be carcinogenic only if all following conditions are fulfilled: fiber length>5µm, diameter <3µm, ratio of length to diameter >3:1.

12. ECOLOGICAL INFORMATION

Textile glass fiber are made from mineral raw material and do not have essential organic substances. They are not biologically decomposable. Textile glass fiber is ecologically harmless.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose in accordance with federal, state, and local regulations as a solid non-hazardous waste.

14. TRANSPORT INFORMATION

Textile glass fiber are not materials in sense of hazardous material. Therefore there are no special measures

necessary for the transportation and labeling by land, sea or air. Transport in closed vehicles in original packaging to protect from humidity.

15. REGULATORY INFORMATION

U.S. Federal Regulations

Toxic Substances Control Act (TSCA): All components of this product are included on the TSCA inventory.

SARA Section 311/312 (40 CFR 370) Hazard Categories for silicone: Acute: Yes, Chronic: No, Fire: No, Pressure: No.

EPA, RCRA 40 CFR, Part 261, 1990: Non-hazardous

CERCLA: Not listed

SARA Title III: Exempt by definition

PA Right-to-Know: Less than reportable quantity

TSCA Inventory: Exempt per section 8(a), 710.2(f), and 704.5(a)

CA Proposition 65: Insignificant trace quantity

MA Right-to-Know: Less than reportable quantity

NJ Right-to-Know: Less than reportable quantity

16. OTHER INFORMATION

Prepared by: Peter Zhou

Issue Date: 8/26/2015

Disclaimer:

Lewco Specialty Products, Inc. makes no warranty of any kind regarding the accuracy or completeness of the information contained herein. Users should independently determine the suitability and completeness of information from all sources for their particular purpose (s). While this data is presented in good faith and believed to be accurate, it should be considered only as a supplement to other information gathered by the user. It is the User's responsibility to assure the proper use and disposal of these materials as well as the safety and health of all personnel who may work with or otherwise come in contact with these materials.