Bus: (780) 454-8558 Fax: (780) 452-2747

CALCIUM SILICATE BLOCK INSULATION

Flat and Scored (3V)

LIST PRICES PER SQUARE FOOT: Subject to Trade Discounts.

| TYPE 1 | I PRESSED - 1 | Flat | Scored (3V) | | | |
|----------------------|---------------|----------|-------------|--------|----------|---------|
| (TYPE 2 P | RESSED - 1700 | 12" Wide | 12" Wide | | | |
| Nominal ⁻ | Thickness | Sq.Ft. | Lbs. | Cu.Ft. | CBLMF | CBLMV |
| Imperial | Metric | /Ctn. | /Ctn. | /Ctn. | \$/SF | \$ / SF |
| 1.0 | 25.0 | 54 | 65 | 5.00 | \$ 12.22 | \$ - |
| 1.5 | 40.0 | 36 | 69 | 5.00 | \$13.52 | \$13.78 |
| 2.0 | 50.0 | 27 | 65 | 5.00 | \$17.16 | \$18.10 |
| 2.5 | 65.0 | 21 | 66 | 5.00 | \$21.58 | \$23.40 |
| 3.0 | 76.2 | 18 | 66 | 5.00 | \$27.30 | \$27.82 |

Carton Outside Dimensions: 19" Wide x 12.5" Deep x 36.3" High = 5.00 Cubic Feet.

Scored & Bevelled (3V) Standard Stock is filter pressed with a V-groove of 9 degrees.

| ANGLE OF DEGREE SUGGESTED FOR DIFFERENT OUTSIDE DIAMETERS OF INSULATION | | | | | | | |
|---|------------|-----------|--------------------|--|--|--|--|
| Form | Score | Degree of | O.D. of Insulation | | | | |
| (V-Groove process) | On Centers | Score | on Pipe or Vessel. | | | | |
| 1200 Pressed | 3" | 9 | * 37" to **56" | | | | |
| 1200 Special Order | 3" | 6 | * 57" to **144" | | | | |
| 1200 Special Order | 6" | 6 | *144" to **248" | | | | |

^{*} Optimum fit is at this joint measurement. Please note that the use of smaller sizes than those listed will cause the joint on the surface to progressively open up as the O.D. decreases. The most efficient fit is obtained by using our fabrication plant's bevelled lags.

^{**} There is an approximate 1/8" void next to substrate (tight on the surface of insulation) at this measurement. Any sizes in the middle range of the measurements noted above will have a an approximate 1/16" void.

| FLAT BEVELLED BLOCK FOR MAXIMUM FIT | | | | | | |
|-------------------------------------|---------|---------|---------|--|--|--|
| TANK OD: | 2-4'11" | 5-7'11" | 8-20'0" | | | |
| LAG OD: | 3" | 4" | 6" | | | |

Please call for pricing relating to any fabrication of the calcium silicate block.

All fabrication is completed according to applicable industry standards.

Traced items are cut to the next smaller Nominal pipe size and larger thickness, i.e. NPS 3 1/2" x 1 1/2" is cut to a 3" x 2" specification. advise if alternative fabrication is required.

Elbows, pipe cover and segments are packaged in corrugated cardboard cartons or clear UV resistant plastic bags.

To determine the extent of sizing for any material, please provide our customer service staff with a list of sizes and quantities.

Our sales policy is applicable. Fabricated items are non-returnable. Some sizes are special order and all pricing is provided for informa purposes only. Prices & specifications are subject to change without notice and feel free to contact our office with any questions.

G.S.T. Extra @ 5%.